Accessories for the distribution network

Taps

EAC 08 272855
EAC 09 272856
EAD 08 272857
EAD 09 272858

- Frequency range: 5-2,400 MHz
- Remote feed suitable max. 24 V; 0.5 A (trunk)
- Integrated decoupling diodes (EAC 08/09), current flow direction: OUT → IN
- Insulating capacitor on tap outputs
- Connections: F connectors
- Connection for potential equalisation
- Small dimensions
- Conform to: EN 60728-11 and EN 50083-2
- For indoor mounting

EAC 09

EAD 09

			1-way	1-way	2-way	2-way
Type			**EAC 08**	**EAC 09**	**EAD 08**	**EAD 09**
Order no.			272855	272856	272857	272858
Through loss	5-47 MHz 47-862 MHz 862-2,150 MHz 2,150-2,400 MHz	dB	2.5 1.6 3 4	1.5 1.5 2.7 3.5	3.5 2.5 4.5 5.5	3 2.5 4 5
Tap loss	5-47 MHz 47-862 MHz 862-2,150 MHz 2,150-2,400 MHz	dB	9-12 9-12 10.5-13 12.5-14.5	13.5-16.5 14-16 13.5-17 17-20	9-12 9.5-12.5 9.5-13 12.5-14.5	13.5-16.5 13.5-16.5 13.5-17 17-20
Directional loss	5-47 MHz 47-862 MHz 862-2,150 MHz 2,150-2,400 MHz	dB	15 25 20 15	25 25 25 20	15 25 20 15	25 25 20 15
Decoupling	5-47 MHz 47-862 MHz 862-2,150 MHz 2,150-2,400 MHz	dB	- - - -	- - - -	15 30 25 20	35 35 30 25
Screening factor	5-300 MHz 300-470 MHz 470-950 MHz 950-2,400 MHz	dB	> 85 > 80 > 75 > 55			
Dimensions		mm	55 x 52 x 23			
Packing unit/weight		pc./kg	1 (10, 200)/0.1			